

| Product identification |               |  |  |  |
|------------------------|---------------|--|--|--|
| Adeo Ref               | 89973270      |  |  |  |
| Product EAN            | 3276007329049 |  |  |  |
| Supplier ref           | IPN138        |  |  |  |
|                        |               |  |  |  |

| Template version history |                        |             |                       |   |  |  |
|--------------------------|------------------------|-------------|-----------------------|---|--|--|
| Version                  | Status                 | Date Status | Comments              |   |  |  |
| V.0                      | Under construction     | 20/08/2018  | Template construction |   |  |  |
| V.1                      | Validated construction | 30/09/2019  | Validated Template    |   |  |  |
|                          |                        |             |                       | - |  |  |
|                          |                        | ·           |                       | - |  |  |

## Object

Technical data sheet of products

## Technical data

## «Name and address of Supplier »

Zhejiang Kingdom New Material Group Co., Ltd

NO.38, DESHENG ROAD, HESHAN TOWN, TONGXIANG CITY, JIAXING CITY, ZHEJIANG PROVINCE, CHINA.

## Zhejiang Kingdom New Material Group Co., Ltd

NO.38, DESHENG ROAD, HESHAN TOWN, TONGXIANG CITY, JIAXING CITY, ZHEJIANG PROVINCE, CHINA.

| Name product   | RIGID PLANK CLIC ART INT-EXT<br>WHARTON2 122X18CM/4.5MM/0.55<br>MM 1.54M2                          | Contain battery                                | NO  |
|--|--|--|---|
| Nett Weight in gram<br>(without batteries,<br>without packaging) | 14050g   | Type of battery<br>(Li-ion /<br>Alkalin,)      | /   |
| Accessories included:<br>detailed it                             | Carton box and instructions  | Weight<br>packaging                            | 250g  |
| Size of product:<br>LxWxH  | 1220x180x4.5mm   | Size packaging<br>LxWxH                        | 1233x191x36mm   |
| Size Length<br>Width<br>ISO 24342                                | Deviation≤0,15% of nominal length<br>up to 0.5mm maximum<br>Deviation≤0,10% up to 0.5mm<br>maximum | Squareness<br>and<br>Straightness<br>ISO 24342 | ≤400mm,deviation≤0.25mm;<br>>400mm,deviation≤0.35mm   |
| Overall thickness<br>ISO 24346                                   | Average:4.5mm +0.13/-0.10mm,<br>Individual Value:average+/-0.15mm                                  | Wear layer<br>thickness<br>ISO 24340           | Nominal value + 13 % /-<br>10 %.Individual results shall not<br>differ as follows with regard to the<br>mean value: no more than 0,05<br>mm or 15 % below the mean value, |

|   |              |  | whichever is greater.                       |
|---|--------------|--|---|
| Class(for Europe)<br>ISO 10582 : 2018<br>ISO 10874 : 2012 | 33           | Dimensional<br>stability<br>ISO 23999    | ≤0.15%                                      |
| Curling,mm<br>ISO 23999                                   | ≤1mm         | Chemical<br>resistance<br>ISO 26987      | Resistant                                   |
| Thermal resistance<br>EN12667                             | 0.05(m²·K)/W | Effect of castor<br>chair<br>ISO 4918    | 25 000 cycles, no delamination shall occur. |
| Color fastness to<br>artificial light<br>ISO 105-B02      | 6            | Reaction to fire<br>EN 13501-1           | Bfl-s1                                      |
| Formaldehyde<br>Emission EN717-1                          | E1           | Slip Resistance<br>DIN 51130<br>EN 13893 | ≥R9<br>DS                                   |

Remark: The main technical features could be adjusted by supplier based on different kinds of products.

Photo