





L

 12.		BS 18 L BS 1800 L Plus	BS 18 L Quick	SB 18 L
	*1)Serial Number	02321..	02320..	02317..
U	V	18	18	18
n <sub>0</sub>	/min, rpm	1	0 - 450	0 - 450
		2	0 - 1800	0 - 1800
M <sub>1</sub>	Nm (in-lbs)	25 (221)	25 (221)	25 (221)
M <sub>3</sub>	Nm (in-lbs)	50 (442)	50 (442)	50 (442)
M <sub>4</sub>	Nm (in-lbs)	1	1,5 - 6 (13,3 - 53,1)	1,5 - 6 (13,3 - 53,1)
D <sub>1</sub> max 	mm (in)		10 ( <sup>3</sup> / <sub>8</sub> )	10 ( <sup>3</sup> / <sub>8</sub> )
D <sub>2</sub> max 	mm (in)		20 ( <sup>25</sup> / <sub>32</sub> )	20 ( <sup>25</sup> / <sub>32</sub> )
D <sub>3</sub> max 	mm (in)	2	-	10 ( <sup>3</sup> / <sub>8</sub> )
s	/min, bpm		-	27000
m	kg (lbs)		1,6 (3.5)	1,6 (3.5)
G	UNF(in)		1/2" - 20 UNF	1/2" - 20 UNF
D <sub>max</sub>	mm (in)		13 ( <sup>1</sup> / <sub>2</sub> )	13 ( <sup>1</sup> / <sub>2</sub> )
a <sub>h, ID</sub> /K <sub>h, ID</sub>	m/s <sup>2</sup>		-	21,5/ 1,5
a <sub>h, D</sub> /K <sub>h, D</sub>	m/s <sup>2</sup>		2,8 / 1,5	2,8 / 1,5
a <sub>h, S</sub> /K <sub>h, S</sub>	m/s <sup>2</sup>		< 2,5 / 1,5	< 2,5 / 1,5
L <sub>pA</sub> /K <sub>pA</sub>	dB(A)		77 / 3	89 / 3
L <sub>WA</sub> /K <sub>WA</sub>	dB(A)		88 / 3	100 / 3



M

CE \*2) 2014/30/EU, 2006/42/EC, 2011/65/EU  
 \*3) EN 60745-1:2009+A11:2010, EN 60745-2-1:2010, EN 60745-2-2:2010, EN 50581:2012

2020-07-06, Bernd Fleischmann  
 Direktor Produktentstehung & Qualität (Vice President Product Engineering & Quality)  
 \*4) Metabowerke GmbH - Metabo-Allee 1 - 72622 Nuertingen, Germany

