Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SanicoPolux

Supplier's address: Sanico Electronics Polska Sp. z o.o., Okólna 45, 05-270 Marki Marki mazowieckie, PL

Model identifier: 209399

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS			
Light source cap-type	MR11					
(or other electric interface)						
Mains or non-mains:	NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	No			
Product parameters						

Parameter	Value	Parameter	Value			
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	2	Energy efficiency class	F			
Useful luminous flux (ϕ use), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	150 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000			
On-mode power (P _{on}), expressed in W	2,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	_			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80			
Outer Height	36	Spectral power	See image			
dimensions Width	35	distribution in the	in last page			

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	35	range 250 nm to 800 nm, at full-load			
Claim of equiva	lent power ^(a)	-	If yes, equivalent power (W)	-		
			Chromaticity coordinates (x and y)	-		
Parameters for directional light sources:						
Peak luminous i	intensity (cd)	-	Beam angle in degrees, or the range of beam angles that can be set			
Parameters for LED and OLED light sources:						
R9 colour rende	ering index value	-	Survival factor	-		
the lumen main	itenance factor					
(a)	101					

(a)'-' : not applicable;

(b)'-' : not applicable;