Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark	: SanicoPolux
-------------------------------	---------------

Supplier's address: Sanico Electronics Polska Sp. z o.o., Okólna 45, 05-270 Marki Marki

mazowieckie, PL

Model identifier: 306524

Type	of light	source:
------	----------	---------

LED	Non-directional or directional:	DLS
LED STRIP		
NMLS	Connected light source (CLS):	No
No	Envelope:	-
No		
No	Dimmable:	No
	LED STRIP NMLS No No	directional: LED STRIP NMLS Connected light source (CLS): No Envelope: No

Product parameters

		1 Todact parar		
Parameter		Value	Parameter	Value
	General product parameters:			
0,	mption in on- 00 h), rounded st integer	28	Energy efficiency class	F
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	2 300 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode prespressed in W	oower (P _{on}),	28,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	-
	dby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	2	Spectral power	See image
dimensions	Width	10	distribution in the	in last page

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) Claim of equiva	Depth lent power ^(a)	5 000 -	range 250 nm to 800 nm, at full-load If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	- -
	Para	meters for direction	nal light sources:	
Peak luminous intensity (cd) -		Beam angle in degrees, or the range of beam angles that can be set	-	
Parameters for LED and OLED light sources:				
R9 colour rende	ering index value	-	Survival factor	-
the lumen main	tenance factor	-		

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;